
# TATA STEEL



## RoofDek D46

## Colorcoat Steel 220 N/mm<sup>2</sup>

(not including \$280 Interior Liner)



#### **Ultimate Section Properties to Eurocode3**

			Broad flange i	n compression	Narrow flange	in compression	100 mm Bearing on steel beam				
Nominal Thickness	Design Thickness	Weight	Moment Capacity	Moment of Inertia	Moment Capacity	Moment of Inertia	Transverse Res	Shear Capacity			
mm	mm	kg/m²	kNm/m	cm4/m	kNm/m	cm4/m	Internal Rw kN/m	End Rw kN/m	kN/m		
0.68	0.64	7.20	2.32	27.61	2.46	29.57	17.72	4.13	34.24		

Imposed load - deflection limit span / 200

Span	Thickness	SPAN (metres)															
Condition	mm	2.30	2.40	2.50	2.60	2.70	2.80	2.90	3.00	3.10	3.20	3.30	3.40	3.50	3.60	3.70	3.80
Single	0.68	1.76	1.54	1.35	1.20			-	-	-	-	-	-	-	-	-	-
Double	0.68	1.88	1.76	1.64	1.53	1.44	1.35	1.27	1.20	1.13	1.07	1.01	0.96	0.91	-	-	-
Multi	0.68	2.28	2.13	1.99	1.86	1.75	1.64	1.55	1.46	1.38	1.31	1.24	1.18	1.12	1.06	0.99	

### Safe Wind Suction (negative) Loads (kN/m²)

Wind suction load - deflection limit span / 90

Span	Thickness	SPAN (metres)															
Condition	mm	2.30	2.40	2.50	2.60	2.70	2.80	2.90	3.00	3.10	3.20	3.30	3.40	3.50	3.60	3.70	3.80
Single	0.68	2.52	2.32	2.14	1.99			-	-	-	-	-	-	-	-	-	-
Double	0.68	2.39	2.20	2.03	1.88	1.75	1.63	1.52	1.42	1.34	1.26	1.18	1.12	1.06	-	-	-
Multi	0.68	2.97	2.73	2.52	2.34	2.17	2.02	1.89	1.77	1.66	1.56	1.47	1.39	1.31	1.24	1.18	

**NOTES** Black figures are stress limited, the load shown is the ultimate load divided by 1.5.

Blue figures are deflection limited.

Red figures indicate that deck length exceeds 12m the maximum advisable. Consider extended end laps

n-12 Calculations are to Eurocode, however additional checks such as fixings are required

**T: +44 (0)845 30 88 330** A construction line load 2 kN/m has been allowed for.

**E: roofdek@tatasteel.com**Deck self weight has been allowed for, so does not have to be included in applied loads